



SEALOCRETE PLA LTD Greenfield Lane
Rochdale OL11 2LD Tel: 01706 352255, Fax 01706 860880

C/SFB

Vv6

TECHNICAL DATA SHEET TDS244
PUBLISHED JANUARY 2003

ACRYLIC PRIMER UNDERCOAT

DESCRIPTION

A high quality, water thinnable wood primer, based on an acrylic polymer system, to provide a coating for priming and/or coating. The product contains inhibitors to prevent rust staining and is resistant to the ingress of soluble salts.

MAIN USES

Priming and undercoating of both interior and exterior wood, building board, dry plaster and hardboard.

BENEFITS

- * Excellent adhesion
- * Excellent opacity
- * Superior filling properties
- * Smooth finish for reduced brush marking

TECHNICAL INFORMATION

Surface Dry	2 – 4 hours @ 20°C
Recoatable	After 4 hours @ 20°C
Coverage	11 – 14 m ² per litre (Depending on substrate porosity)

COLOURS: White

PACKAGING

750ml, 2.5 litres, 5 litres

SURFACE PREPARATION

All surfaces must be clean, dry and free from loose and flaking material, dirt, grease etc.

Any previously painted surfaces should be suitably abraded prior to painting.

Knotting should be applied to knots or resinous areas prior to painting.

APPLICATION

Supplied ready to use by brush, roller or airless spray. Thinning is not normally required, but up to 10% water may be added for application to particularly porous surfaces.

For spray application please refer to the Technical Department for advice.

Acrylic Primer is not suitable for metal substrates. For metal use Sealocrete Red Oxide Primer.

Do not apply in temperatures less than 5°C or where high humidity may cause surface condensation.

CLEANING

Clean all equipment immediately after use with water.

STORAGE

Protect from frost. Store in a cool dry place away from direct sunlight

Shelf life is at least 12 months when stored as directed in undamaged and unopened containers.

HEALTH & SAFETY

Keep out of reach of children. In case of contact with eyes, wash immediately with copious amounts of water. Remove splashes from skin with soap and water.

We endeavour to ensure that any advice, recommendation or information we may give in product literature is accurate and correct. However, we have no control over the circumstances in which our product is used and it is therefore important that the end user satisfy himself by prior testing that the product is suitable for his specific application and that the actual conditions of use are suitable. Accordingly, no responsibility can be accepted, or any warranty given by ourselves, our representatives, agents or distributors, other than that the product as supplied by us will meet our written specification. Products are sold subject to our standard conditions of sale and each purchaser and end user should at all times ensure that he has consulted our latest product instructions and safety information.

