



SEALOCRETE PLA LTD Greenfield Lane
Rochdale OL11 2LD Tel: 01706 352255, Fax 01706 860880

CI/SfB

Vn6

TECHNICAL DATA SHEET
PUBLISHED AUGUST 2003

ALL WEATHER SEALANT

DESCRIPTION

Sealocrete ALL WEATHER SEALANT is a single component co-polymer sealant that adheres to most wet or dry building surfaces. It is supplied as translucent or black and can be applied in wet or dry conditions for emergency repairs. It is permanently flexible and may be over painted.

USES

Sealocrete ALL WEATHER SEALANT provides a waterproof seal and can be used in all weather conditions. It will seal most common building materials and can be used as an emergency sealant for leaks. ALL WEATHER SEALANT is over-paintable with most paints and stains. It is applied with the use of a sealant gun.

COVERAGE

Approximately 10 linear metres of bead at 6 mm diameters.

PACKAGING

Sealocrete ALL WEATHER SEALANT is available in standard size cartridges.

METHOD OF USE

Surfaces should be free from loose dirt, oil, grease contamination and standing water.

Fungicidal growth should be removed and the area treated with Sealocrete Fungicidal Wash. Metal surfaces should be wire brushed to remove loose scale or dust.

Apply the sealant as a continuous bead firmly into joints and gaps to ensure good contact. If required smooth sealant with a tool wetted with soapy water within 5 minutes of application.

Drying time 48 to 72 hours or longer depending on bead diameter.

CLEANING OF TOOLS

Immediately after use all tools should be cleaned with Sealocrete Thinners No. 3.

STORAGE

ALL WEATHER SEALANT should be stored in a cool, dry place away from sources of ignition or naked flames. Shelf life is a minimum of 12 months in unopened sealed containers.

HEALTH & SAFETY

Sealocrete ALL WEATHER SEALANT is flammable, therefore do not breathe fumes, do not smoke when using the product. Also ensure adequate ventilation.

For further information please refer to the Health & Safety Data Sheet.

We endeavour to ensure that any advice, recommendation or information we may give in product literature is accurate and correct. However, we have no control over the circumstances in which our product is used and it is therefore important that the end user satisfy himself by prior testing that the product is suitable for his specific application and that the actual conditions of use are suitable. Accordingly, no responsibility can be accepted, or any warranty given by ourselves, our representatives, agents or distributors, other than that the product as supplied by us will meet our written specification. Products are sold subject to our standard conditions of sale and each purchaser and end user should at all times ensure that he has consulted our latest product instructions and safety information.

