



SEALOCRETE PLA LTD Greenfield Lane  
Rochdale OL11 2LD Tel: 01706 352255, Fax 01706 860880

Cl/SfB
VvG

TECHNICAL DATA SHEET TDS 29  
PUBLISHED JANUARY 2003

## CONTRACT EMULSION PAINT

### DESCRIPTION

SEALOCRETE CONTRACT EMULSION PAINT is a high quality paint available in two grades, matt and silk. In 90% of cases the CONTRACT EMULSION is recommended as a one-coat application.

### USES

The CONTRACT EMULSION PAINT has been specifically formulated for use by professionals. It is made using the best polymers and pigments available and can be used on all interior walls and ceilings. CONTRACT EMULSION PAINT can be applied to slightly damp surfaces and gives a long lasting tough finish with superior opacity and scratch resistance.

### ADVANTAGES

- \* GOOD COVERAGE  
90% of applications only one coat required.
- \* GOOD FINISH  
Long lasting and tough.
- \* EASY TO USE  
By brush, roller or spray
- \* EASY TO CLEAN  
Water based, therefore washes off with water.
- \* ISO 9002 Quality Assured Firm.

### PRODUCT DATA

Colour: BRILLIANT WHITE or MAGNOLIA  
Coverage: Approx 10m<sup>2</sup>/litre depending on the porosity of the surface.

### METHOD OF USE

#### Preparation

Ensure all surfaces are at least surface dry and free from dirt, grease and loose debris.

Fill all cracks and hole using ALL PURPOSE FILLER. Any mould or algae should be treated prior to use with FUNGICIDAL WASH. Allow all areas to dry.

#### Application

CONTRACT EMULSION is best applied at standard room temperature.

#### By Brush:

If a number of coats are required, CONTRACT EMULSION can be thinned using one part water to eight parts paint.

#### By Roller:

Can be thinned as above if more than one coat is required. use any synthetic roller to suit the surface.

#### Conventional Spray:

If needed, thin to one part water to eight parts of paint.

#### Airless Spray:

Thin one part water to ten parts paint. Use spray at working pressure of 138 bars.

Tip Size: 0.39 - 0.43mm at an angle of 60 to 80 degrees.

CONTRACT EMULSION is touch dry in approximately one hour. If needed, re-coat after 2- 4 hours.

Clean all brushes and tools in water after use.

Keep lid tightly sealed and protect from frost.

## **STORAGE**

### ***PROTECT FROM FROST***

If stored in a cool, dry place in original unopened containers, the shelf life is 12 months.

## **PACKAGING**

Available in 5 litre and 10 litre buckets.

## **HANDLING**

Use only in well ventilated areas. Keep out of the reach of children and animals. Wash off skin with soap and water. In case of eye contact, rinse immediately with plenty of water. For further information please refer to the relevant Product Safety Data Sheet.

*We endeavour to ensure that any advice, recommendation or information we may give in product literature is accurate and correct. However, we have no control over the circumstances in which our product is used and it is therefore important that the end user satisfy himself by prior testing that the product is suitable for his specific application and that the actual conditions of use are suitable. Accordingly, no responsibility can be accepted, or any warranty given by ourselves, our representatives, agents or distributors, other than that the product as supplied by us will meet our written specification. Products are sold subject to our standard conditions of sale and each purchaser and end user should at all times ensure that he has consulted our latest product instructions and safety information.*

