




SEALOCRETE PLA LTD Greenfield Lane
Rochdale OL11 2LD Tel: 01706 352255, Fax 01706 860880



TECHNICAL DATA SHEET TDS007
PUBLISHED SEPTEMBER 2002

DECORATORS SEALANT

DESCRIPTION

DECORATORS SEALANT is a single component, water-based acrylic sealant which, when exposed to the atmosphere, cures to form a strong, tough, flexible seal.

USES

DECORATORS SEALANT is primarily intended as an interior filler and sealant which can be overpainted if required.

- * Filling cracks in plaster, cement, concrete and timber.
- * Sealing around doors and window frames.
- * Sealing between walls, skirting boards, dry linings, wall boards and ceilings.
- * Repairing existing cracked joints.

ADVANTAGES

- * Easy to apply in convenient cartridge form.
- * Excess material easily washed off with water.
- * Can be over-painted.
- * Requires no priming.
- * Adheres to most building substrates.
- * Water based and therefore safer to use than solvent based equivalents.

PRODUCT DATA

Service temperature: -10°C to +70°C

Application temperature: -5°C to 35°C

Cure time: Fully cured 24 - 48 hours depending on relative humidity and temperature.

Joint dimensions: Minimum width 5mm
Maximum width 25mm

Slump: Nil on 20mm x 20mm channel

Colour: White only

Coverage/usage rate:

Rectangular Joint Size mm	Approx metres per cartridge
6 x 6	8.6
10 x 6	5.3
10 x 10	3.2
25 x 12	1

METHOD OF USE

Ensure all surfaces are dry, free from dust, dirt and loosely adhering materials. In most cases priming is not necessary, but porous surfaces such as concrete and plaster should be primed by diluting one part sealant with two parts of water and allowing to dry. Sealant is applied using a standard skeleton gun and tooled using a moist knife. Mask surrounding areas for cleaner application and remove tape immediately after sealant has been applied. Surplus material can be removed using a damp cloth.

The sealant may be over-painted after skinning, usually approximately after 3 hours for emulsion paints, but sealant must be allowed to dry for a minimum of 10 hours before gloss paints are applied.

NOTE:

Avoid any contact with moisture such as condensation for 12 hours after application. Protect cartridge and freshly applied sealant from frost.

STORAGE

If stored as received in a cool dry place between 5°C and 25°C the shelf life is 12 months. Protect from frost.

PACKAGING

Available in polyethylene cartridges containing approximately 310mls.

HANDLING

This product is non-hazardous in normal use. Keep away from eyes and mouth, wash off with soap and water. Do not ingest. For further information refer to the relevant Health and Safety Data Sheet.

We endeavour to ensure that any advice, recommendation or information we may give in product literature is accurate and correct. However, we have no control over the circumstances in which our product is used and it is therefore important that the end user satisfy himself by prior testing that the product is suitable for his specific application and that the actual conditions of use are suitable. Accordingly, no responsibility can be accepted, or any warranty given by ourselves, our representatives, agents or distributors, other than that the product as supplied by us will meet our written specification. Products are sold subject to our standard conditions of sale and each purchaser and end user should at all times ensure that he has consulted our latest product instructions and safety information.

