



SEALOCRETE PLA LTD Greenfield Lane
Rochdale OL11 2LD Tel: 01706 352255, Fax 01706 860880

CI/SfB

TECHNICAL DATA SHEET TDS099
PUBLISHED SEPTEMBER 2002

FIX AND GROUT

DESCRIPTION

FIX AND GROUT is a ready mixed, thin-bed, water-resistant adhesive and grouting material, suitable for fixing ceramic tiles to most types of interior surface. Suitable for showers, kitchens and bathrooms.

USES

Advantages

- * Easy to apply.
- * Good water resistant properties.
- * Can be used as a grout as well as an adhesive.

PACKAGING

Available in 0.5, 1.0, 2.5, 5.0 and 10 litre buckets.

TECHNICAL DATA

Colour:	White only
Coverage:	
Notched Trowel Method	up to 1 m ² / litre
Solid Bed Method	up to 0.3 m ² / litre

METHOD OF USE

Preparation of surfaces

The surface to be tiled must be flat, dry, sound, free from oil, grease dust and other contaminations. Porous surfaces should be primed with 1 part SEALOBOND, diluted with 5 parts water and allowed to dry. The background temperature should be above 5°C.

APPLICATION

Notched-Trowel Method

The adhesive should be spread onto the wall with a trowel to a depth of 3 mm. This operation is immediately followed by "combing" the adhesive with a notched trowel, for example, one having 6 mm x 6 mm notches at 25 mm centres. This will produce a series of parallel ribs of adhesive onto which the dry tiles should be pressed. Spread only sufficient material for about 15 minutes tiling work, i.e. about 1/2 m².

Solid Bed Method

Use in situations where damp conditions will prevail after tiling is completed, e.g. in a domestic shower. Apply adhesive to the wall in a uniform layer, about 3 mm thick, and comb the surface very lightly. Press the tiles firmly into this layer of adhesive to ensure solid-bedding and absence of voids behind the tiles.

Grouting

Tile joints may be grouted as soon as the adhesive has set, usually after 6 hours on porous backings. Using a damp cloth or sponge, firmly press FIX AND GROUT into the joints and smooth grout surface. Allow grout to dry for about 15 minutes and then clean the tiles with a dry cloth.

Cleaning of Equipment and Surfaces

Surface adhesive must be removed whilst still wet using a damp cloth. Immediately after use, clean tools with warm water.

STORAGE

PROTECT FROM FROST

Non-flammable. Shelf life is up to 12 months when stored in a dry place within the temperature range 5 to 30°C.

HANDLING

This product is non-hazardous in normal use. Avoid prolonged contact with skin, wear gloves if skin is sensitive. If contact occurs, wash immediately with soap and water. Eyes should be well rinsed with clean water. Ensure adequate ventilation whilst in use.

We endeavour to ensure that any advice, recommendation or information we may give in product literature is accurate and correct. However, we have no control over the circumstances in which our product is used and it is therefore important that the end user satisfy himself by prior testing that the product is suitable for his specific application and that the actual conditions of use are suitable. Accordingly, no responsibility can be accepted, or any warranty given by ourselves, our representatives, agents or distributors, other than that the product as supplied by us will meet our written specification. Products are sold subject to our standard conditions of sale and each purchaser and end user should at all times ensure that he has consulted our latest product instructions and safety information.

