



SEALOCRETE PLA LTD Greenfield Lane
Rochdale OL11 2LD Tel: 01706 352255, Fax 01706 860880

CI/SfB

TECHNICAL DATA SHEET TDS049
PUBLISHED SEPTEMBER 2002

FLEXIBLE ADDITIVE

DESCRIPTION

FLEXIBLE ADDITIVE is a low viscosity, water based, polymer emulsion for use with all SEALOCRETE cement based tile adhesives and grouts.

USES

FLEXIBLE ADDITIVE improves the adhesion of tile adhesives to denser impervious surfaces such as glazed tiles, concrete and primed timber. Water permeability is reduced for wet situations, both internally and externally. FLEXIBLE ADDITIVE imparts extra flexibility so that the adhesive can cope with substrates subject to slight movement or vibration.

ADVANTAGES

- * Promotes Adhesion
- * Reduces Permeability.
- * Increases flexibility

TECHNICAL DATA

General

Colour:	Low viscosity White Emulsion
Usage:	2.5L per 20kg cement based adhesive or grout

PACKAGING

Available in 1 litre and 2.5 litre bottles.

METHOD OF USE

Preparation and Priming

All surfaces to be tiled should be clean, dry and free from loose particles, grease, oil and dirt. Prime the surface with SEALOBOND PVA diluted 1:5 with water and allow to dry overnight.

Mixing and Application

Add 2.5 litres of FLEXIBLE ADDITIVE to 20kg of adhesive or grout in the mixing vessel. Add water and mix to a smooth, creamy consistency. For smaller mixes, the quantity of FLEXIBLE ADDITIVE should be proportioned accurately or the overall performance may be impaired.

Apply the modified adhesive or grout as per the normal instructions for the product.

Please note: FLEXIBLE ADDITIVE may affect the set and working time of a mix.

STORAGE

If stored in a cool dry place in unopened containers, the shelf life is 12 months. Once opened, use as soon as possible.

HANDLING

Keep away from children and animals. Wash splashes from eyes and skin immediately with clean water.

Do not ingest.

The wearing of gloves is recommended.

For further information, see Health and Safety data sheet.

We endeavour to ensure that any advice, recommendation or information we may give in product literature is accurate and correct. However, we have no control over the circumstances in which our product is used and it is therefore important that the end user satisfy himself by prior testing that the product is suitable for his specific application and that the actual conditions of use are suitable. Accordingly, no responsibility can be accepted, or any warranty given by ourselves, our representatives, agents or distributors, other than that the product as supplied by us will meet our written specification. Products are sold subject to our standard conditions of sale and each purchaser and end user should at all times ensure that he has consulted our latest product instructions and safety information.

