



SEALOCRETE PLA LTD Greenfield Lane  
Rochdale OL11 2LD Tel: 01706 352255, Fax 01706 860880

CI/SfB	
	Zn5

TECHNICAL DATA SHEET  
PUBLISHED FEBRUARY 2005

## FLEXIBLE WIDE JOINT GROUT

### DESCRIPTION

FLEXIBLE WIDE JOINT GROUT is a cement based compound for grouting around ceramic tiles for both internal and external situations. It is water-resistant when set and will not wash out of joints.

### USES

A tile grout for use in joints up to 20mm wide. Ideally suited for areas subject to slight movement or vibration.

### ADVANTAGES

Excellent durability-  
Easy to mix and apply.

### PRODUCT DATA

Colour: Grey.  
Coverage: Approximately 2m<sup>2</sup>/kg at 3mm joints on tiles 152mm x 152mm x 5mm.

### METHOD OF USE

Allow at least 24 hours from completion of tiling before grouting and ensure joints are clean and free from contamination. Mix the FLEXIBLE WIDE JOINT GROUT powder with clean water to a lump free creamy paste.

Using a rubber squeegee or grouting trowel, work the grout into the joints around the tiles. Work it in firmly to avoid gaps. Remove any excess with a damp cloth whilst it is still wet; polish the tiles with a dry cloth after completion of the grouting. We recommend grouting 1 m<sup>2</sup> at a time.

Finished grouting should be protected from rain, frost or water until it has cured. If used outside it is also important that it does not dry out too soon, as can happen on very hot days and in direct sunshine.

### STORAGE

If stored as received in original unopened bags in a cool dry place, the shelf life is 6 months.

### PACKAGING

Available in 10kg bags.

### HANDLING

FLEXIBLE WIDE JOINT GROUT is a cementitious product and therefore a potential skin irritant. In case of contact with eyes and skin wash with clean water and obtain medical attention. Keep out of reach of children and animals. For further information refer to the relevant Health and Safety Data Sheet.

*We endeavour to ensure that any advice, recommendation or information we may give in product literature is accurate and correct. However, we have no control over the circumstances in which our product is used and it is therefore important that the end user satisfy himself by prior testing that the product is suitable for his specific application and that the actual conditions of use are suitable. Accordingly, no responsibility can be accepted, or any warranty given by ourselves, our representatives, agents or distributors, other than that the product as supplied by us will meet our written specification. Products are sold subject to our standard conditions of sale and each purchaser and end user should at all times ensure that he has consulted our latest product instructions and safety information.*

