



SEALOCRETE PLA LTD Greenfield Lane  
Rochdale OL11 2LD Tel: 01706 352255, Fax 01706 860880

CI/SfB

Yr4

TECHNICAL DATA SHEET TDS246  
PUBLISHED JANUARY 2002

# LIGHT FILLER

## DESCRIPTION

Sealocrete LIGHT FILLER is a white, ready to use, polymer based product for filling cracks and holes in many building materials. It is quick drying and easy to use, giving a smooth finish which does not require sanding.

## USES

LIGHT FILLER is specifically designed for filling cracks and holes in plaster, wallboard, concrete, brickwork and wood. A single application fills deep repairs without sagging or slumping. for indoor and outdoor use, but must be protected from rain and frost until fully dried.

## ADVANTAGES

Quick drying. No sanding. No sagging. No shrinkage. Lightweight and very white.

## METHOD OF USE

### Preparation

Surfaces should be dry, sound, clean, free from dirt and dust or any other loose flaky material.

### Application

Stir thoroughly to a smooth paste. If Filler is too dry add a few drops of water and stir to the desired consistency. Apply using a small trowel or filler knife and press firmly into the crack or hole and smooth off.

*We endeavour to ensure that any advice, recommendation or information we may give in product literature is accurate and correct. However, we have no control over the circumstances in which our product is used and it is therefore important that the end user satisfy himself by prior testing that the product is suitable for his specific application and that the actual conditions of use are suitable. Accordingly, no responsibility can be accepted, or any warranty given by ourselves, our representatives, agents or distributors, other than that the product as supplied by us will*

## Drying Time

Dries white within 15 minutes. (Drying time will vary depending on ambient conditions, size and thickness of repair.)

Protect from rain and frost whilst drying.

For best results use Sealocrete's Acrylic Primer Undercoat before over-painting. LIGHT FILLER must be over-painted when used on exterior surfaces.

## PACKAGING

Sealocrete LIGHT FILLER is available in 0.5 litre and 1 litre sizes.

## CLEANING

Tools and equipment should be cleaned with water immediately after use.

## STORAGE

LIGHT FILLER should be stored in a cool, dry place. Shelf life is a minimum of 12 months in unopened, sealed containers.

## HEALTH AND SAFETY

LIGHT FILLER is non hazardous in normal use. For further information please refer to the Health & Safety Data Sheet before using this product.

*meet our written specification. Products are sold subject to our standard conditions of sale and each purchaser and end user should at all times ensure that he has consulted our latest product instructions and safety information.*

