



CI/SfB			
		Yr4	

TECHNICAL DATA SHEET TDS129  
 PUBLISHED SEPTEMBER 2002

# MASONRY PAINT

## DESCRIPTION

SEALOCRETE MASONRY PAINT is a tough, durable, exterior coating available in smooth and sand textured grades. It contains a fungicide to give a long lasting decorative finish.

## USES

SEALOCRETE MASONRY PAINT can be used on rough cast concrete, sand/cement renders, pebble dash and some bricks. It is not recommended for use on glossy or non porous surfaces.

## ADVANTAGES

- **RESISTANT COATING**  
 Contains biocide to protect against unsightly growths.
- **DECORATIVE**  
 Available in a range of nine colours.
- **SAFE & EASY TO USE**  
 Water based, no solvent fumes and easy to clean equipment.

## TECHNICAL DATA

Appearance:	Coloured Paint
Viscosity:	300 - 450 poise @ 20°C
Specific Gravity:	1.28 – 1.48

## COVERAGE

Will depend on the texture and porosity of the surface to be covered.

Smooth Masonry Paint :

Typically 8 – 12m<sup>2</sup> per litre per coat on rendering.

Textured Masonry Paint :

Typically 3 – 6.5m<sup>2</sup> per litre per coat.

## COLOURS

Brilliant White, Magnolia, Ivory, Sandstone, Misty Grey, Lakeland Green, Dusty Pink, Etruscan Red and Black

## PACKAGING

MASONRY PAINT is available in 5 litre plastic pails and in 10 litre buckets – White and Magnolia only.

## METHOD OF USE

### Preparation of Surfaces

All surfaces should be clean, dry and free from loose or flaking material. Remove loose material by scraping or brushing with a stiff brush. Make good any broken or spalled concrete with a suitable cement or resin based repair mortar (Sealocrete CEMENTPATCH or EPOXYPATCH range).

Any cracks which may lead to moisture penetration should be filled.

Chalking, weathered and porous surfaces should then be treated with a liberal application of STABILISING SOLUTION. This should be allowed to dry for a minimum of 12 hours before painting.

Any contamination by mould, mildew or fungi should be removed by scraping and then treating with FUNGICIDAL WASH as directed.

### Application

Stir thoroughly before use. Do not thin. Apply by brush, roller or conventional spray.

It is recommended that two coats are applied for maximum durability, leaving 24 hours between coats. Do not apply when there is a risk of rain, frost or if the temperature falls below 5°C.

*We endeavour to ensure that any advice, recommendation or information we may give in product literature is accurate and correct. However, we have no control over the circumstances in which our product is used and it is therefore important that the end user satisfy himself by prior testing that the product is suitable for his specific application and that the actual conditions of use are suitable. Accordingly, no responsibility can be accepted, or any warranty given by ourselves, our representatives, agents or distributors, other than that the product as supplied by us will meet our written specification. Products are sold subject to our standard conditions of sale and each purchaser and end user should at all times ensure that he has consulted our latest product instructions and safety information.*

Where more than one pack of a single colour is to be used, check the batch numbers. If they differ, mix all containers together thoroughly to avoid any colour variation.

### CLEANING

Tools and equipment should be cleaned with water immediately after use.

### STORAGE

MASONRY PAINT should be stored in a cool, dry place away from frost. Shelf life is a minimum of 12 months in unopened, sealed containers.

### HEALTH AND SAFETY

MASONRY PAINT is not classified as hazardous. In case of skin or eye contact, rinse with plenty of water. For further information please refer to the Health & Safety Data Sheet.

