



SEALOCRETE PLA LTD Greenfield Lane
Rochdale OL11 2LD Tel: 01706 352255, Fax 01706 860880

C1 | SfB | Vv5

TECHNICAL DATA SHEET TDS 59
PUBLISHED JANUARY 2003

OXIDE FINISH AGRICULTURAL PAINT

DESCRIPTION

A High Quality Oxide Finish with good obliteration suited for painting structural steel, metal, metal sheeting, cladding etc., where an Economical but Durable Decorative Finish is required.

PROPERTIES

Based on a Modified Linseed/Soya Oil Alkyd resin system with a flash point above 32°C (90°F). Recommended for the protection of wood and metal substrates not subject to chemical attack.

PRODUCT DATA

Coverage: Approximately 65 square metres per 5 litres, depending upon substrate.

Application: Brush Roller, Conventional or Airless Spray.

Drying Time: Touch dry 4-6 hours
Hard dry 16 hours.
Recoatable 16-24 hours.

METHOD OF USE

Preparation

All substrates must be clean and free from grease and oil. Any such patches must be thoroughly cleaned using a suitable degreasing solution and the surface allowed to dry.

Previously painted surfaces must be sound and all flaking material removed prior to painting. If compatibility is in question then it is recommended that a small area is tested first.

Do not apply in cold or damp conditions.

APPLICATION

Brush:

Thinning not normally required except on bare/untreated substrates.

Roller:

Thinning not normally required except on bare/untreated substrates. Roller should be of the short pile variety.

Airless spray:

Thinning ratio: up to 1 litre of White Spirits to 5 litres paint. Consult equipment manual for usage depending on conditions at point of application..

Spray tip aperture - 0.33 to 0.38mm
(13-15 thou)

Spray tip angle - 50 - 70

Minimum working pressure - 2000 psi

Recommended System:

One coat of Oxide Primer followed by one/two coats Oxide Finish depending upon finish/obliteration required.

CLEANING

Clean all equipment with White Spirit immediately after use.

COLOUR AVAILABILITY

Tile Red, Cypress Green, Slate Grey, Blue Grey, Juniper Green, Black.

PACK SIZE

5ltrs & 20ltrs

STORAGE

Store in a dry place away from heat and flame.
Shelf life is at least 12 months when stored as directed in undamaged and unopened containers.

HEALTH & SAFETY

As with all Paints and Coatings, as long as reasonable standards and safe working are maintained then there should be no major hazards in the handling of this product.

- * Flammable
- * Keep away from sources of ignition
- * Keep away from children
- * Ensure adequate ventilation
- * Avoid breathing excessive vapours
- * Avoid breathing spray
- * When spraying, always wear proper respiratory equipment and protective clothing
- * Avoid contact with eyes. In case of contact with eyes, irrigate thoroughly with water and seek medical advice.
- * Avoid contact with skin
- * Wash splashes from skin using a recognised skin cleanser
- * Do not empty into drains or water courses
- * Contains white spirits
- * Contains no added lead

We endeavour to ensure that any advice, recommendation or information we may give in product literature is accurate and correct. However, we have no control over the circumstances in which our product is used and it is therefore important that the end user satisfy himself by prior testing that the product is suitable for his specific application and that the actual conditions of use are suitable. Accordingly, no responsibility can be accepted, or any warranty given by ourselves, our representatives, agents or distributors, other than that the product as supplied by us will meet our written specification. Products are sold subject to our standard conditions of sale and each purchaser and end user should at all times ensure that he has consulted our latest product instructions and safety information.

