



SEALOCRETE PLA LTD Greenfield Lane  
Rochdale OL11 2LD Tel: 01706 352255, Fax 01706 860880

CI/SfB		
	Zn5	

TECHNICAL DATA SHEET TDS 63  
PUBLISHED JANUARY 2003

## ROAD LINE PAINT

### DESCRIPTION

A flexible, hard wearing road lining paint with excellent intercoat adhesion properties. It may be applied to concrete and asphalt surfaces and has good chemical resistance, making it suitable where salt and chemicals used to control ice and snow are used.

### PROPERTIES

Sealocrete Road Line Paint is based on a chlorinated rubber system.

### PRODUCT DATA

Coverage:	Approximately 10m <sup>2</sup> /5 litres or 78 metres @ 100 mm width
Drying Time:	Normally 15-20 mins depending upon substrate and method of application. Flash point 23°C.

### PREPARATION

**Before commencing painting, all surfaces should be clean, dry and free from grease and friable material. Lack of adequate surface preparation is usually the cause of flaking and poor adhesion.**

New laid concrete should be fully dry before paint is applied, and all laitence removed. Asphalt is a non porous substrate and therefore relies upon good film adhesion. Surfaces should be clean and dry.

Whilst Sealocrete Road Line Marking Paint is suitable for asphalt, care should be taken when asphalt is new and because of the possibility of bleed. White is not recommended on new asphalt.

### APPLICATION

Application by brush or airless spray.

### BRUSH

Thinning not required. Because of the fast dry nature of the product, apply liberally and quickly.

### AIRLESS SPRAY

Spray tip angle: consult equipment manual.  
Dependent upon width of strip required.  
Spray tip aperture: 15 thou (0.388mm)  
Min working pressure: 2000 psi.

### CLEANING

Clean all equipment immediately with Xylene.

### AVAILABILITY

White and Yellow, packed in 5 litre cans.

### HEALTH & SAFETY

As with all Paints and Coatings, as long as reasonable standards and safe working are maintained then there should be no major hazards in the handling of this product.

- \* Flammable
- \* Keep away from sources of ignition
- \* Keep away from children
- \* Ensure adequate ventilation
- \* Avoid breathing excessive vapours
- \* Avoid breathing spray
- \* When spraying, always wear proper respiratory equipment and protective clothing.

## **ROAD LINE PAINT page 2.**

- \* Avoid contact with eyes. In case of contact with eyes, irrigate thoroughly with water and seek medical advice.
- \* Avoid contact with skin
- \* Wash splashes from skin using a recognised skin cleanser
- \* Do not empty into drains or water courses
- \* Contains Xylene, Isomers of Benzene, Carbon Tetrachloride.

## **STORAGE LIFE**

Shelf life is at least 12 months when stored as directed in undamaged and unopened containers.

*We endeavour to ensure that any advice, recommendation or information we may give in product literature is accurate and correct. However, we have no control over the circumstances in which our product is used and it is therefore important that the end user satisfy himself by prior testing that the product is suitable for his specific application and that the actual conditions of use are suitable. Accordingly, no responsibility can be accepted, or any warranty given by ourselves, our representatives, agents or distributors, other than that the product as supplied by us will meet our written specification. Products are sold subject to our standard conditions of sale and each purchaser and end user should at all times ensure that he has consulted our latest product instructions and safety information.*

