



SEALOCRETE PLA LTD Greenfield Lane  
Rochdale OL11 2LD Tel: 01706 352255, Fax 01706 860880

CI/SfB

Yt4

TECHNICAL DATA SHEET TDS165  
PUBLISHED SEPTEMBER 2002

## ROOF & GUTTER SEALANT

### DESCRIPTION

ROOF & GUTTER SEALANT is a versatile black, water resistant, flexible, non slumping gap filler used in the repair of roofs and guttering. It has excellent adhesion to most surfaces including concrete, brickwork, glass, asphalt and metal.

### USES

Sealing between roof flashings and brickwork.

Sealing horizontal joints in concrete and asphalt where they will not be subjected to heavy loads or trafficking

Sealing cracks in asphalt and roofing felt.

Sealing leaking gutters and roof service pipes.

Sealing joints between metal eg. Tanks, metal frames. If used on tanks time should be allowed for the solvent to completely evaporate (approx 6 weeks) before filling with water.

### ADVANTAGES

- \* Easy to use sealant
- \* Good weather resistance
- \* Will adhere to a wide variety of substrates and uneven surfaces
- \* Long lasting seal.

### TECHNICAL DATA

Colour	Black only
Tack Free Time @ 25°C Full Cure @ 25°C; 50%RH	24 hours 6 – 8 weeks
Adhesion	Excellent to most building materials
Application Temperature Service Temperature	+5°C to +35°C -20 to +70°C

Note: Cure rates are temperature dependant

### COVERAGE

Cartridge will provide 10 – 12 metres of a 6mm diameter bead.

### PACKAGING

ROOF & GUTTER SEALANT is supplied in Standard size 310ml. cartridges

### METHOD OF USE

#### Surface Preparation

Before application, thorough preparation is essential. The surfaces must be completely dry and free from all traces of dirt, dust, grease, previous sealants (if any), and any other foreign matter

Where appropriate masking tape can be applied either side of a joint to assist in maintaining a neat appearance.

Extrude from the cartridge using a standard skeleton gun, ensuring adequate contact between sealant and substrate – do not apply below 5°C.

## **STORAGE**

ROOF & GUTTER SEALANT should be stored in cool, dry conditions, away from frost or direct sunlight. The product will have a shelf life of 12 months when stored in these conditions in original unopened containers.

## **HANDLING**

ROOF & GUTTER SEALANT is solvent based and appropriate measures should be taken when using this product. Remove all sources of ignition, do not smoke, ensure adequate ventilation and avoid contact with skin. Please refer to the relevant Health and Safety Data Sheet for further information before using this product.

*We endeavour to ensure that any advice, recommendation or information we may give in product literature is accurate and correct. However, we have no control over the circumstances in which our product is used and it is therefore important that the end user satisfy himself by prior testing that the product is suitable for his specific application and that the actual conditions of use are suitable. Accordingly, no responsibility can be accepted, or any warranty given by ourselves, our representatives, agents or distributors, other than that the product as supplied by us will meet our written specification. Products are sold subject to our standard conditions of sale and each purchaser and end user should at all times ensure that he has consulted our latest product instructions and safety information.*

