



SEALOCRETE PLA LTD Greenfield Lane
Rochdale OL11 2LD Tel: 01706 352255, Fax 01706 860880

CI/SfB

TECHNICAL DATA SHEET TDS201
PUBLISHED SEPTEMBER 2002

SEALOGRIP ACRYLIC

DESCRIPTION

SEALOGRIP ACRYLIC is a ready to use tile adhesive which is suitable for fixing ceramics and expanded polystyrene tiles to most surfaces. It exhibits superior non slip properties, eliminating the need for battens even with large ceramic tiles, whilst allowing a reasonable period of time for correcting fixing errors.

SEALOGRIP ACRYLIC is easy to apply and is suitable for use in all interior situations including bathrooms and kitchens. It is not suitable for permanently damp conditions, areas subjected to complete immersion, floors or metal tiles.

SEALOGRIP ACRYLIC meets the performance requirements of BS5980 : 1980 "Specification for adhesives for use with ceramic tiles and mosaics."

ADVANTAGES

- Easy to use - light and easy to spread.
- Excellent non slip properties
- Long open time - allows large areas to be tiled in one go.
- Low odour
- Meets the requirements of BD5890 for Type 2 Class B

PACKAGING

Available in 10 litres only.

TECHNICAL DATA

Colour	Light Grey
Coverage: (approx.)	
Notched Trowel Method	1m ² per litre
Solid Bed Method	0.3m ² per litre

METHOD OF USE

Preparation of surfaces

Surfaces must be sound, clean, dry and free from grease and oil. Newly plastered walls must be left at least four weeks before tiling to ensure good adhesion. Cement/sand mortar renderings must be left at least fourteen days, and should be dry when fixing begins.

Absorbent surfaces such as plaster and renders should be primed first with Sealobond PVA at a dilution of 1 : 5 PVA to water.

Do not tile in temperatures below 5°C.

APPLICATION

Dry Situations

Spread adhesive evenly to a depth of 3mm. Comb with a suitable notched trowel, ideally having notches 6mm x 6mm at 25mm centres. This will give a series of ribs onto which the dry tiles should be firmly pressed home, using a slight twist action.

Damp Situations

Spread adhesive evenly to a depth of 3mm to form a thin solid bed. Secure the tiles firmly again using a slight twist action, ensuring no voids remain. Do not apply more adhesive than can be used in twenty minutes.

SEALOGRIP ACRYLIC will not stain tiles, but all surplus adhesive must be removed with a damp cloth before the adhesive dries. Wash hands and tools in cold water.

Grouting

Careful attention must be paid to the grouting operation. A satisfactory job can be seriously impaired through insufficient grouting. All areas must be allowed to dry for at least twenty-four hours before grouting can commence. Wet areas such as showers should be grouted with a suitable water resistant grout. Showers must not be used until fourteen days after grouting.

Expansion Joints

Reference must be made to the relevant British Standard Codes of Practice for the installation of expansion joints when tiling large areas.

STORAGE

PROTECT FROM FROST

If stored in a cool dry place in original unopened containers the shelf life is in excess of twelve months.

HEALTH & SAFETY

This product is non-hazardous in normal use. Avoid prolonged contact with skin, wear gloves if skin is sensitive. If contact occurs, wash immediately with soap and water. For further information please refer to the product Health & Safety Data Sheet.

We endeavour to ensure that any advice, recommendation or information we may give in product literature is accurate and correct. However, we have no control over the circumstances in which our product is used and it is therefore important that the end user satisfy himself by prior testing that the product is suitable for his specific application and that the actual conditions of use are suitable. Accordingly, no responsibility can be accepted, or any warranty given by ourselves, our representatives, agents or distributors, other than that the product as supplied by us will meet our written specification. Products are sold subject to our standard conditions of sale and each purchaser and end user should at all times ensure that he has consulted our latest product instructions and safety information.

