



SEALOCRETE PLA LTD Greenfield Lane
Rochdale OL11 2LD Tel: 01706 352255, Fax 01706 860880

CI/SfB

Yu2

TECHNICAL DATA SHEET TDS212
PUBLISHED SEPTEMBER 2002

STABILISING SOLUTION

DESCRIPTION

STABILISING SOLUTION is a clear, ready to use water based treatment for bonding and priming surfaces prior to painting.

USES

STABILISING SOLUTION is recommended for use as a pre-treatment for surfaces which are old, perished, chalky or porous. It can be used on concrete, plaster, plasterboard, cement renders, pebbledash etc.

ADVANTAGES

- * **SAFE & EASY TO USE**
Ready to use polymer emulsion, can be applied by brush, roller or spray.
- * **VERSATILE**
May be used on many different substrates.

PACKAGING

STABILISING SOLUTION is available in 2.5 litre and 5 litre packs.

COVERAGE:

Typically 6m² per litre, depending on substrate porosity and texture.

METHOD OF USE

Surface Preparation

Any algae or mould must first be removed by mechanical means and/or with a FUNGICIDAL WASH.

Surfaces must also be cleaned to remove any loose, friable or flaking material.

Do not apply STABILISING SOLUTION when the temperature is below 5°C or when rain or frost is imminent. The product can be applied to damp substrates.

APPLICATION

The product should not be diluted, simply stir well. Apply by brush, airless spray or roller direct from the container. A second application may be necessary with surfaces which are particularly porous or powdery. Allow surface to dry for up to 12 hours between coats or before decorating.

Cleaning of Tools

Clean equipment with soap and water after use.

STORAGE

STABILISING SOLUTION must be kept in cool, dry conditions away from frost and direct sunlight. This product will have a shelf life of 12 months if stored in these conditions in original unopened containers.

HEALTH & SAFETY

STABILISING SOLUTION is not classified as hazardous. Please refer to the Health & Safety Data Sheet for detailed information on the handling of this product.

We endeavour to ensure that any advice, recommendation or information we may give in product literature is accurate and correct. However, we have no control over the circumstances in which our product is used and it is therefore important that the end user satisfy himself by prior testing that the product is suitable for his specific application and that the actual conditions of use are suitable. Accordingly, no responsibility can be accepted, or any warranty given by ourselves, our representatives, agents or distributors, other than that the product as supplied by us will meet our written specification. Products are sold subject to our standard conditions of sale and each purchaser and end user should at all times ensure that he has consulted our latest product instructions and safety information.

