



SEALOCRETE PLA LTD Greenfield Lane
Rochdale OL11 2LD Tel: 01706 352255, Fax 01706 860880

CI/SfB		
	Yt4	

TECHNICAL DATA SHEET TDS222
PUBLISHED SEPTEMBER 2002

TROWELLING MASTIC

DESCRIPTION

TROWELLING MASTIC is a long life, ready mixed oil based compound. It can be used to replace sand and cement pointing where a superior finish is required or where the joint is too narrow for successful mortar pointing. TROWELLING MASTIC has proved to be an excellent replacement for the old type, site mixed mastics, It is non drip and hardens by oxidation of the oil to form a tough protective skin. It is not suitable for surfaces treated with a microporous paint

USES

Typical applications include:

- * Bedding in door and window frames, in low movement situations
- * For pointing stone and brickwork.

COLOURS

Red and Buff.

COVERAGE / USAGE RATE

1 kg will fill a 9mm x 9mm x 6m square section gap.

PACKAGING

Available in 1kg, 2kg, 5kg, 10kg and 25kg containers

We endeavour to ensure that any advice, recommendation or information we may give in product literature is accurate and correct. However, we have no control over the circumstances in which our product is used and it is therefore important that the end user satisfy himself by prior testing that the product is suitable for his specific application and that the actual conditions of use are suitable. Accordingly, no responsibility can be accepted, or any warranty given by ourselves, our representatives, agents or distributors, other than that the product as supplied by us will meet our written specification. Products are sold subject to our standard conditions of sale and each purchaser and end user should at all times ensure that he has consulted our latest product instructions and safety information.

METHOD OF USE

Prepare all surfaces by brushing down with a hard bristle or wire brush to remove old pointing and other loose or friable material. Dusty or porous surfaces should first be primed with double boiled linseed oil. Apply the mastic with a trowel, putty knife or pointing tool. When pointing, ensure the mastic is forced firmly into place. The hardening time is dependent on weather conditions and temperature. A tough protective skin forms within a few days of application and the mastic can be overpainted if required.

Do not use TROWELLING MASTIC in contact with Bitumen, Tar, Aluminium or microporous treated surfaces.

STORAGE

If stored as received in a cool dry place below 15°C, the shelf life is 6 months. At higher temperature a thick skin may form, although this is not detrimental to the remainder of the mix.

HANDLING

TROWELLING MASTIC is non-hazardous in normal use. Avoid skin and eye contact. Sealant can be removed using industrial hand cleaners. Do not ingest. For further information refer to the relevant Health and Safety data sheet.

