



SEALOCRETE PLA LTD Greenfield Lane
Rochdale OL11 2LD Tel: 01706 352255, Fax 01706 860880

CI/SfB

Yu2

TECHNICAL DATA SHEET TDS102
PUBLISHED FEBRUARY 2005

WIDE JOINT GROUT

DESCRIPTION

WIDE JOINT GROUT is a cement based compound for grouting around ceramic tiles for both internal and external situations. It is water resistant when set and will not wash out of joints. WIDE JOINT GROUT is recommended for joints from 3 mm to 10 mm wide.

USES

As a tile grout for joints 3 mm to 10 mm wide.

TECHNICAL DATA

Colour:	Grey, Brown, Sandstone and Black
Coverage:	Approx. 2m ² / kg at 3 mm joints on tiles 152 mm x 152 mm x 5 mm

METHOD OF USE

Allow at least 24 hours from completion of tiling before grouting and ensure joints are clean and free from contamination. Mix the WIDE JOINT GROUT powder with clean water to a lump free creamy paste – approximately 160ml water to 1kg powder.

The addition of FLEXIBLE ADDITIVE is strongly recommended in areas subject to slight movement or vibration.

Using a rubber squeegee or grouting trowel, work the grout into the joints around the tiles. Work it in firmly to avoid gaps. Remove any excess with a damp cloth whilst it is still wet, polish the tiles with a dry cloth after completion of the grouting. We would recommend grouting 1m² at a time.

It is essential that a small area is tested for colour fastness.

Finished grouting should be protected from rain, frost or water until it has cured. If used outside it is also important that it does not dry out too soon, as can happen on very hot days and in direct sunshine.

STORAGE

If stored as received in original unopened bags in a cool dry place, the shelf life is 6 months.

Packaging

Available in 3 kg, 10 kg and 20 kg bags.

HANDLING

Avoid contact with hands. When skin contact occurs, wash off with clean water. Avoid splashing into eyes. If eye contact occurs, irrigate with water and seek medical advice.

We endeavour to ensure that any advice, recommendation or information we may give in product literature is accurate and correct. However, we have no control over the circumstances in which our product is used and it is therefore important that the end user satisfy himself by prior testing that the product is suitable for his specific application and that the actual conditions of use are suitable. Accordingly, no responsibility can be accepted, or any warranty given by ourselves, our representatives, agents or distributors, other than that the product as supplied by us will meet our written specification. Products are sold subject to our standard conditions of sale and each purchaser and end user should at all times ensure that he has consulted our latest product instructions and safety information.

